

SPC Luxury Vinyl Plank
Outland and
Traverse Collections



Classification:	ASTM F 1700-04 Class III Type B Solid Vinyl Flooring
Size:	7.18"x48.62" / 182.5mm x 1,235mm (3 SKU's): Passage Country Cabin Passage Fallen Timber Passage Vintage 9"x59.75" / 228.6mm x 1517.65mm Embossed in Register (3 SKU's) Outland Chesapeake Outland Woodland Trail Traverse Backcountry Trail
Total Thickness:	3/16" (nominal) / 5mm (4mm SPC + 1mm IXPE Acoustical Underlay)
Wear Layer Thickness:	22 mil / 0.55mm, UV coated with ceramic bead & nano-silver additives
Construction:	Layered - consisting of wear layer, film, core and backing
Edge:	Four-Sided Micro-Bevel
Total # of SKU's:	6 colors
Limited Warranty:	Lifetime Residential, 10 Year Light Commercial
Recycle Content:	100% Virgin Materials. Product can be recycled post-use

www.AscensionFlooring.com

Packaging:	7.18"x48.62"	9"x59.75"
	10 pieces/carton	6 pieces / carton
	24.24 SF (2.25 SM) / carton	22.41 SF (2.10 SM) / carton
	44 cartons / pallet	48 cartons / pallet
	20 pallets / container	20 pallets / container
	41 lbs (18.6 KG) / carton	38.58 lbs (17.5 KG) / carton

Product Testing

Flammability	ASTM D 2859-06/CPSC FF 1-70	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF \geq 0.45
Smoke Density	ASTM E 662-06	< 450
Slip Resistance	ASTM D 2047	Exceeds ADA & OSHA Recommendations
Stain Resistance	ASTM F 925	Pass
Heat Stability	ASTM F 1514	Pass
Light Stability	ASTM F 1515	Pass
Dimensional Stability	ASTM F 2199	Pass
Impact Insulation (IIC) (6" concrete)	ASTM E 429-09	51 dB w/
Delta IIC (6" concrete)	ASTM E 2179-09	23 dB
Residual Indentation	ASTM F 1914	Pass (1%)
Sound Isolation (IIC)	ASTM E 989	>50 dB
Phthalate Content	EN 14372	Not Detected
Static Load Limit (without IXPE Backing)	ASTM F 970	1,300 PSI



by  SCS certified.